

Measuring probes for GMH 3330 and GMH 3350

Humidity / temperature



Humidity/temperature:

TFS 0100 E

(0.0 ... 100.0 % RH)

Humidity/temperature probe, exchangeable

Specification:	
Measuring ranges:	
Humidity:	0.0 ... 100.0 % RH (rec. range of application: 11 ... 90 % RH)
Temperature:	-40.0 ... +120.0 °C (attention: working temperature of electronics!)
Accuracy: (at nominal temperature = 25 °C)	
Humidity:	±2.5 % RH
Temperature:	±0.5 °C
Sensors:	
Humidity:	capacitive polymer humidity sensor
Temperature:	Pt1000, 1/3 DIN
Electronics:	
PC board with amplifier and data memory for sensor data (calibration, etc.) integrated in probe handle.	
Working temperature:	
-25 ... +60 °C (handle and electronics) -40 ... +100 °C (for short time up to +120 °C) (sensor head and tube)	
Relative humidity:	
0 ... +100 % RH	
Dimensions:	
Probe tube: Ø 14 x 119 mm, plastic handle: Ø 19 x 135 mm, approx. 1 m PVC connection cable with 6-pin Mini-DIN-plug	
Weight:	
approx. 90 g	

**GFN-SET1**Humidity reference cells for ~33 and ~76 %RH,
probe adapter and robust carry case

Features:	
Humidity reference cells works on the basis of physiochemical processes. A specific value of relative humidity adjusts itself over a saturated salt solution. The test chamber is separated from the solution by a diaphragm so that the sensor under test is protected against contamination by the solution. The test container can be used in all mounted positions.	

Accessories and spare parts:	
GFN 33	humidity reference cell for ~33 % RH, incl. adapter
GFN 76	humidity reference cell for ~76 % RH, incl. adapter

Surface temperature:

GOF 400VE

(p.r.t. page 20)

Quick-response surface probes for walls, floors etc.

GTF 300

(p.r.t. page 22)

Quick-response basic thermocouple probe for universal applications
(surface measurement)

Flow speed



Water:

STS 005

(0.05 ... 5.00 m/s)

Flow measuring probe with snap-on head, exchangeable

Specification:	
Sensor type:	windmill-type anemometer
Measuring range:	0.05 ... 5.00 m/s (water)
Accuracy:	±1 % of range ± 3 % of meas. value (at nominal temperature = 25 °C)
Permiss. angle flow:	±20°, without additional measuring faults
Working temperature:	-10 ... +80 °C
Relative humidity:	0 ... +100 % RH (non-condensing)
Dimensions:	Probe head: Ø 11 x 15 mm, tube: Ø 15 mm, overall length 165 mm, required insertion opening: Ø 16 mm, approx. 5 m PVC connection cable with 6-pin Mini-DIN-plug
Weight:	approx. 75 g

Air:

STS 020

(0.55 ... 20.00 m/s)

Flow measuring probe with snap-on head, calibrated and exchangeable.

Specification:	
Sensor type:	windmill-type anemometer
Measuring range:	0.55 ... 20.00 m/s (air)
Accuracy:	±1 % of range ± 3 % of meas. value (at nominal temperature) = 25 °C)
Permiss. angle flow:	±20°, without additional measuring faults
Working temperature:	-10 ... +80 °C
Relative humidity:	0 ... +100 % RH (non-condensing)
Dimensions:	Probe head: Ø 11 x 15 mm, tube: Ø 15 mm, overall length 165 mm, required insertion opening: Ø 16 mm, approx. 5 m PVC connection cable with 6-pin Mini-DIN-plug
Weight:	approx. 75 g

Accessories and spare parts:	
STE 005	Spare snap-on head for STS 005
STE 020	Spare snap-on head for STS 020
GTS	GTS Telescopic rod (overall length 1 m) Please specify when ordering - no retrofit assemblage possible!



picture shows GTS with assembled STS 020