


NE-M1-CL7 Series LED Dome Signal Light; One Signal Light with 7 LED color combinations provide multiple solutions with years of maintenance-free operation.

FEATURES


- · Seven multicolored LEDs.
- Low power consumption to increase energy efficiency.
- High protection rating for outdoor use.
- Color-coded wires for easy wiring.
- Applications are suitable for AGV units, small tooling machines, control panels, etc.
- One unit can make colors in Red, Yellow, Green, Blue, Light Blue, Purple and White.
- Has the CE mark and conforms to the requirements for the EC directive.


Dimensions (Unit: mm) **Mounting Dimensions** Wire Entry Hole Mounting Hole M16×P1.5 2-ø4.5 **Specifications** Operating Operating Humidity Protection Rated Mass Model Temperature Range Rating NE-M1-CL7 | 12 - 24V DC -30 C - +50 C 90% or less IP66/IP67 55g

How to Order



Wiring






■ Diverse Color Possibilities WHITE YELLOW GREEN







The white colored lens dispays various colors much clearer and uniformly diffuses the light source.

■ Environmental **Resistant Characteristics**



High Protection for an IP rating of 66 and 67, it can be used in environments with higher humidities and dust exposure.

Color Chart	
Wiring	LED Color
RED	RED
GREEN	GREEN
BLUE	BLUE
RED/GREEN	YELLOW
BLUE/GREEN	LIGHT BLUE
RED/BLUE	PURPLE
RED/GREEN/BLUE	WHITE

Model Name	NE-M1-CL7
Rated Voltage	12V DC~24V DC
Operating Voltage Range	10 V DC~30 V DC
Operating Temperature Range	-30 °C to + 50°C (90% RH or less)
Protection Rating	IP66/IP67
Display Color	7 Colors