

Explosion-safe LED Warning light AR-044

With fixed cable

Features

- ATEX certified
- Suitable for use in gas and dust environments, Zone 2 and 22
- 15 LEDs
- Light color red, yellow / amber or green
- Continuous lighting or blinking, user selectable
- Anodized aluminum housing
- Polycarbonate (PC) impact-resistant window
- Ingress protection level IP65
- 24 VDC, 4 Watt
- Fixed cable, 5 meters



II 3 G Ex mc IIC T4 Gc
II 3 D Ex mc IIIC T135°C Dc



Description

Artidor's omnidirectional explosion-safe LED signal light is designed for use under normal weather conditions.

The 15 latest generation LEDs ensure a clearly perceptible visual signal. Dependent on the execution, the light will burn continuously or it blinks at a frequency of 1 Hertz. The warning light can be ordered either with a radial cable connection or with a connection on the back of the lamp. This makes the lamp highly suitable for use as a warning light on control cabinets.

The connection cable has a standard length of 5 meters.

The Artidor LED warning light is explosion-safe and certified in accordance with European Directive 2014/34/EU (ATEX 114) and is CE marked.



ZONE 2/22



Explosion-safe LED Warning light AR-044

With fixed cable



Technical data

Explosion safety:	II 3 G Ex mc IIC T4 Gc, II 3 D Ex mc IIIC T135°C Dc
European directives:	2014/34/EU (ATEX 114), 2014/30/EU (EMC)
Applied standards:	EN 60079-0:2018 and EN 60079-18:2015 / A1:2017
Light color:	Red (625 nm), yellow / amber (610 nm) or green (530 nm)
Light intensity:	195 lm
Material:	Anodized aluminum housing, 4 mm impact-resistant polycarbonate window
Degree of protection:	IP65 according to EN 60529
Supply voltage:	24 VDC \pm 10%
Nominal current:	160 mA @ 24 VDC
Connection:	Fixed cable, 4 x 0,5 mm ² , length 5 m
Earth connection:	External, stainless steel, 4 mm ²
Ambient temperature:	-20 °C to +60 °C
Dimensions:	Ø95 x 41 mm (excl. cable gland)
Assembly:	Stainless steel bracket
Weight:	830 gram



Order code

AR-044 / 0 3 1 - R

Light color

R = Red, 625 nm
Y = Yellow / amber, 610 nm
G = Green, 530 nm

Housing material

1 = Anodized aluminum

Lighting mode

3 = Continuous or blinking, user selectable – 4-wire connection

Cable position

0 = Radial (default, see picture)
1 = Axial (at request)

